

# Robust aber kompakt: 3 m Sturzschutz – IP67 – 280 g



- Windows CE® 6.0 R3
- 3 m Sturzschutz und IP67
- 280 g leicht und besonders ergonomisch
- 6,9 cm QVGA-Touchdisplay
- Smart Card Reader / Writer

| Spezifikationen            |  |  |   |
|----------------------------|--|--|---|
| Modell                     | DT-X8-10E  | DT-X8-20E  |   |
| <b>CPU</b>                 | Marvell® PXA320 624MHz                                   |  |   |
| <b>Betriebssystem</b>      | Microsoft® Windows® Embedded CE 6.0 R3 Englische Version |  |   |
| <b>Strapazierfähigkeit</b> | <b>Sturzschutz</b>                                       | 3.0m   |   |
|                            | <b>Staub/Spritzwasserschutz</b>                          | IP67 (Kompatibel mit IEC60529 Standard)  |   |
|                            | <b>Betriebs-temperatur</b>                               | -20°C bis 50°C   |   |
| <b>Speicher</b>            | <b>RAM</b>   | 128MB  |   |
|                            | <b>ROM</b>   | 256MB (Frei für User: Ca. 160MB)   |   |
| <b>Display</b>             | <b>LCD</b>   | Blanview® TFT Farb-LCD mit Touchscreen 5,9 cm (2,7 Inch) QVGA (240x320 Pixel)  |   |
|                            | <b>Anzeige</b>   | Anzeige 1: Batteriewechsel-Status<br>Anzeige 2: Kabellose Kommunikation und Scan-Status  |   |
| <b>Eingabe</b>             | <b>Tastatur</b>  | 23 Tasten, inkl. num. Tasten, CLR-Taste, Abschlusstaste, Cursor-Taste, Power-Taste, Trigger-Taste Fn key, F1 zu F8 Taste, L/R-Taste  |   |
|                            | <b>Scannertasten</b>                                     | 3 (Mitte, Links und rechts)  |   |
|                            | <b>Touchscreen</b>                                       | Ja (Resistiver Typ)  |   |
| <b>Scanner</b>             | <b>Typ</b>   | Laser-Scanner  | C-MOS Imager  |
|                            | <b>Auflösung</b>   | 0.127mm  | 1D: 0.15mm, Stacked: 0.169mm, Matrix: 0.25mm  |
|                            | <b>1D</b>  | GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded, Code128/GS1-128 (UCC/EAN128), Code93, Code39, EAN8, EAN13, UPC-A, UPC-E, Codabar (NW-7), IATA, MSI, Interleaved 2of5 (ITF), Industrial 2 of 5 | GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded, Code128/GS1-128 (UCC/EAN128), Code93, Code39, Code32, Code11, EAN8, EAN13, UPC-A, UPC-E, Codabar (NW-7), IATA, MSI, Interleaved 2 of 5 (ITF) |
|                            | <b>Stacked</b>   | GS1 DataBar Stacked, GS1 DataBar Expanded Stacked  | GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Expanded Stacked, Code49, PDF417, Micro PDF, Composite, Codablock F, TLC39  |
|                            | <b>Matrix</b>  |  | Aztec, DataMatrix, Maxicode, QR Code, microQR   |
| <b>Wireless LAN</b>        | <b>Standard</b>  | IEEE 802.11b (Maximum: 11Mbps), IEEE 802.11g (Maximum: 54Mbps)   |   |
|                            | <b>Sicherheit</b>  | WPA2 / AES   |   |
| <b>Interface</b>           | <b>Bluetooth®</b>  | Bluetooth® Version 2.0+EDR kompatibel  |   |
|                            | <b>Karte</b>   | microSD Speicherkarte (SDHC) x 1   |   |
|                            | <b>USB Port</b>  | Version 1.1 (Host/Client)  |   |
|                            | <b>Audio</b>   | Mikrofon: integriert (monaural), Lautsprecher: integriert (monaural)   |   |
| <b>Power</b>               | <b>Main Power</b>  | Large-capacity lithium-ion battery pack (Operating period: Approx. 20 hours*)  | Large-capacity lithium-ion battery pack (Operating period: Approx. 18 hours*)   |
|                            | <b>Memory Backup</b>                                     | Lithium-Batterie (wiederaufladbar) integriert  |   |
| <b>Vibrator</b>            | Standard   |  |   |
| <b>Größe (BxHxT)</b>       | Ca. 65,7 (57,4*) x 187,0 x 32,4 (35,0*) mm *Griff außen  |  |   |
| <b>Gewicht</b>             | 282g (Inklusive großem Akku)                             |  |   |



Windows® and Windows® Embedded are registered trademarks of the Microsoft Corporation, USA. The Bluetooth trademark is owned by Bluetooth SIG, USA and licensed to Casio Computer Co. Ltd. Other product- or company names are either trademarks or registered trademarks of the respective owners. This publication carries product description without obligation and is not to be seen as a firm offer. Specifications and design are subject to change without notice.

